



JCB HYDRAULIC COMPACTORS

The JCB Compactor is a hydraulically operated attachment powered from the carrier machine's hydraulics. It comprises a hydraulic motor coupled to an offset weight assembly which is mounted on a steel baseplate. Operation of the motor spins the offset weight, causing the plate to vibrate. An inbuilt protection valve eliminates damaging pressure surges and all hydraulic components are situated inboard of the Compactor's side plates for maximum protection. To allow compaction of deeper trenches, an optional bolt-on extension leg is available. The compactor is suitable for direct or Quickhitch mounting and is supplied with Quick Release tall hoses and an Owner's Manual.

Part Number	Item	2CX 10ft	2CX 12ft	3C 14ft	3CX/ 4CX14	3C 15ft	3CX/ 4CX15	3CX/ 4CX17
980/03200	Compactor	•	•	•				
980/32000	Compactor				•	•	•	•
980/A1595	Footplate				•	•	•	•

FEATURES

- For trench reinstatement and general ground compaction.
- Dipper mounting ensures the operator is fully protected from the effects of vibration.
- Connects to the high flow circuit, the unit only requires 24 lpm.
- Inbuilt protection valve safeguards the unit from hydraulic pressure surges.
- Suitable for direct or quickhitch mount.

Item	Width (in)	Length (in)	Optimum Machine Downforce (lb)	Force Input (lbf ft)	Amplitude (in)	Centrifugal Force (lbf)	Required Oil Flow (gallons)
980/03200	12	29	1543	31.7	0.15	3664.4	6.34
980/32000	12	29	1543	31.7	0.15	3664.4	6.34